




● Cuponal Standard Supply

Standard supply availability of Cuponal busbars

Cuponal Size Selector																									
thickness mm	width mm																								
	10	12	15	16	18	20	24	25	28	30	32	34	38	40	42	50	60	63	65	75	80	92	90	100	120
3	✓					✓		✓																	
4	✓			✓		✓		✓		✓				✓											
5	✓	✓	†			✓†		✓		✓†				✓†		✓	✓					✓			
6						✓		✓	✓	✓				✓		✓	✓			✓	✓				✓
6.3		✓		✓		✓		✓	✓		✓		✓	✓		✓		✓	✓		✓	✓		✓	✓
8				✓		✓		✓		✓		✓		✓		✓	✓			✓	✓		✓	✓	
10	†	✓	†✓			✓†		✓†		✓†				✓†		✓†	✓†	✓		✓	✓†			✓†	✓
12		†			†	✓	†			†				✓	†	✓	✓							✓	✓
12.5																		✓							
15							†							✓		✓	✓								✓
16											✓														

Round section	
	Available diameters (mm)
	5, 6.3, 8, 10, 11, 12, 14, 18, 20, 24, 35, 40

Special sections			
	L-section (mm)		D-section (inches)
	70 x 32 x 10 50 x 30 x 5 35 x 30 x 5		3 x 1 D 2.5 x 1 D 2.5 x 1 DD 80 x 15 D (mm)
		DD - radius both edges	

Dimensional specifications for standard supply Cuponal

Bar length	
Range	Tolerance mm
Standard length	+9 -0
Cut to length	+2 -2
Straightness: 2mm per 1000mm	
Maximum length: call with your requirements	

Rectangular section				
Width mm		Thickness tolerance mm ±		
Range	Tolerance ±	3 ≤ t ≤ 6	6 < t ≤ 10	10 < t ≤ 16
w ≤ 10	0.08	0.07	0.08	
10 < w ≤ 18	0.1	0.07	0.09	0.1
18 < w ≤ 30	0.15	0.07	0.09	0.1
30 < w ≤ 50	0.2	0.09	0.1	0.12
50 < w ≤ 80	0.25	0.11	0.12	0.15
80 < w ≤ 120	0.3	0.12	0.15	0.18
Maximum width: 120mm				

Round section	
Diameter ø mm	
Range	Tolerance ±
ø ≤ 3	0.02
3 < ø ≤ 6	0.03
6 < ø ≤ 12	0.05
12 < ø ≤ 25	0.08
25 < ø ≤ 40	0.12
Max diameter: 40mm	